


Plan**14943000610 Zastłona prysznicowa PLAN uni****PRODUKTU****RYSUNEK WYMIAROWY****OPIS PRODUKTU**

100% trevira, 80 g/m², pionowe szwy
wzmocnione pierścienie ze stali nierdzewnej
odstęp pomiędzy pierścieniami około 200 mm
waga pierścieni około 50 g na metr bieżący zastłony
impregnowana, grzyboodporna, antybakteryjna,
antystatyczna, prać w 30°, kurczliwość około 1-2%
testowane na obecność substancji szkodliwych zgodnie
ze standardami Oeko – Tex Standard 100
kompletna z pierścieniami na zastłonę, białe

POWIERZCHNIA

antracyt/8 oczek

WYMIAR

1800 x 1400 mm

SPECYFIKACJE

KEUCO shower curtain PLAN uni, 14943000110, 55-2/16" x 70-14/16",
anthracite, 8 eyelets
100% trevira, 0.0165 lb/ft², vertical seams
reinforced for stainless steel eyelets,
distance between eyelets approx. 7-7/8",
weighted seam 1.76 oz per 39-3/8"
impregnated, fungizid, antibacterial, anitstatic,
washable at 30° C / 86° F, shrinkage appr, 1-2%,
tested acc, to OEKO-Tex Standard 100
complete with curtain rings, white

Information concerning the measurements:

All dimensions refer to the actual finish size,

In order for the shower curtain not to touch the bottom of the bath
tub or the floor we recommend the following:

Distance between the floor and the bottom edge of the curtain appr, 1-3/16",

Distance between the centre of the curtain pole and the top edge of the
curtain

appr, 1-9/16",

Please allow appr, 1,3 to 1,5 times curtain pole length when
calculating the required width of the curtain,