# PRODUCT DATA SHEET



# Plan

### 14944000110 Shower curtain PLAN uni

# **PRODUCT**



#### **DRAWING**

Keine Zeichnung erforderlich

No Drawing neccessary

# **PRODUCT ATTRIBUTES**

100% trevira, 80g/m², vertical seams reinforced for stainless steel eyelets Distance between eyelets appr. 200 mm Weighted seam 50 g per meter impregnated, fungicide, antibacterial, antistatic, washable at 30°, shrinkage appr. 1-2% tested acc. to OEKO-Tex Standard 100 complete with white curtain rings

# **SURFACE**

white/8 eyelets

#### **DIMENSION**

2000 x 1400 mm

# **SPECIFICATIONS**

KEUCO shower curtain PLAN uni, 14944000110, 1400 x 2000 mm, white, 8 eyelets

100% trevira, 80g/m², vertical seams reinforced for stainless steel eyelets, distance between eyelets approx. 200 mm, weighted seam 50 g per metre impregnated, fungizid, antibacterial, anitstatic, washable at 30°, shrinckage appr, 1-2%, tested acc, to OEKO-Tex Standard 100 complete with curtain rings, white

calculating the required width of the curtain

Information concerning the measurements:
All dimensions refer to the actual finish size,
In order for the shower curtain not to touch the bottom of the bath
tub or the floor we recommend the following:
Distance between the floor and the bottom edge of the curtain appr, 30 mm,
Dinstance between the centre of the curtain pole and the top edge of the
curtain
appr, 40 mm,
Please allow appr, 1,3 to 1,5 times curtain pole length when